



MONIL[®]-KE gel

Viscous cold lacquer remover

Item no. 4753



MONIL[®]-KE gel is a special product to remove paint

- dissolves synthetic paint, emulsion paint, primers and graffiti,
- gentle to metal, wood, concrete and other mineral substances,
- recommended to be spread on parts to remove paint.

MONIL[®]-KE gel is safe and reliable

- guaranteed free of poisonous substances and CKW (e.g. methylene chloride),
- removes several layers of paint in one process,
- for use in paintshops, workshops and craft businesses.



Areas of application and recommended dilution:

Undiluted

MONIL[®]-KE gel is suitable to remove paint from all types of small and big parts.

Spread with a brush or scraper a 1 – 2 mm thick layer, let it act for 5 – 30 minutes and abrade afterwards with a scraper or jerk off with a high pressure cleaner. Keep away from sources of ignition – No smoking. Use only in well ventilated areas.

MONIL[®]-KE gel was developed for the gentle removal of paint from solvent resisting parts. Do not apply on synthetic materials or plastic parts, they may be harmed!

Your HWR-partner on site advises you to a custom-made solution which meets your requirements.

Characterisation:

Appearance:

Colourless gel with a characteristic odour.

Ingredients:

Preparation from tensides, water soluble solvents, additives and thickening agents.

pH value:

Neutral (in aqueous solution).

This product data sheet has been created according to the most current standard of technology. We do however not guarantee for correctness and completeness. No liability for damages due to improper application. update July 2015

HWR CHEMIE GmbH[®], Moosfeldstraße 7, D-82275 Emmering

Telefon 08141 / 51 03 0 • Fax 08141 / 51 03 50 • E-Mail: info@hwr-chemie.de • www.hwr-chemie.de