



HLR-SUPER

High-performance rust dissolver

Item no. 5030



HLR-SUPER for cases, where other products fail

- outstanding water displacement and penetrating attributes,
- strong dissolver for oil, tar and fat,
- remarkable qualities as anticorrosive and lubricant.

HLR-SUPER saves money, time, energy and the cutting torch

- when loosening corroded and burnt-on screws and bolts,
- for treatment of stiff chains or hinges,
- as a quick aid in industry and workshop.



Areas of application:

Releasing and disassembling of seized bolts and threads: Spray HLR-SUPER on the parts, which have to be released and let it act a few minutes. To avoid the seize up, treat the thread with the special lubricating agent COPPER-LUB 1300 (Item no. 5010) and let it act again a few minutes. Release screw with a short and powerful cant (use a ring flat wrench, to avoid the risk of gliding off). You may also release tightened screws near the exhaust pipe, the brakes or the tie rods in most cases, where other products fail.

Characterisation:

Appearance:

Yellow liquid with an oily smell.

Ingredients:

Preparation from a mixture of mineral oils, spindle oil, MoS₂ and corrosion protecting additives.
Free of AOX and CFC.

This product data sheet has been created according to the most current standard of technology. We do however not guarantee for correctness and completeness. No liability for damages due to improper application. update July 2015

HWR CHEMIE GmbH®, Moosfeldstraße 7, D-82275 Emmering

Telefon 08141 / 51 03 0 • Fax 08141 / 51 03 50 • E-Mail: info@hwr-chemie.de • www.hwr-chemie.de