



MULTI-FILM

Separating agent, sliding agent, silicone-free
Item no. 5112

MULTI-FILM is the flexible helper

- outstanding separating and sliding attributes,
- soil resistant and non resin attributes,
- neutral with other materials and machines.

MULTI-FILM is an all-purpose agent

- for separating tasks in a wide range of temperatures,
- for separating of veneers in joiner's workshops,
- for lubrication of guide rails and locks.



Areas of application and recommended dilution:

Separating agent:

Apply MULTI-FILM undiluted by spraying or razor-thin with a lintfree cloth or sponge.

Suitable as all-purpose separating agent, especially for wood processing businesses. MULTI-FILM is proven in joiner's workshops as a sliding agent for wood processing machines as well as for the application in the veneer press. Excessive glue will be easily and safely removed after veneering. The further processing of wood (varnishing, pickling) will not be affected adversely.

Lubricant:

Suitable for lubrication of drawers, stainless steel parts, door locks, guide rails, gates etc.; MULTI-FILM does not resinify and is easily removable, if required.

Characterisation:

Appearance:

Colourless liquid with a mild scent.

Ingredients:

Preparation from natural oils and aliphatic hydrocarbons.

Free of aromatic hydrocarbons, AOX and CFC.

Temperature resistance:

up to +150 °C.

This product data sheet has been created according to the most current standard of technology. We do however not guarantee for correctness and completeness. No liability for damages due to improper application. update July 2015

HWR CHEMIE GmbH®, Moosfeldstraße 7, D-82275 Emmering

Telefon 08141 / 51 03 0 ▪ Fax 08141 / 51 03 50 ▪ E-Mail: info@hwr-chemie.de ▪ www.hwr-chemie.de