



HWR-Aluzink

Touch up spray

Item no. 5130



HWR-ALUZINK provides maximum protection for iron and steel parts

- heat resistant touch up spray with high aluminium-zinc content,
- provides an elastic, firm base coat, prepared for varnishing,
- prevents from corrosion underneath, also suitable for spot-welding.

HWR-ALUZINK is versatilely used

- for base coating of iron and steel parts,
- for touch-up work on damaged zinc surfaces.



Areas of application:

Undiluted:

Shake well before use, until the steel balls are swinging in the can.

Spray on the surfaces evenly and crosswise and let it dry. The drying time is approx. 20 minutes. HWR-ALUZINK is heat resistant up to approx. 450 °C.

Characterisation:

Appearance:

Aerosol with a characteristic scent.

Ingredients:

Preparation from aerosol propellant, epoxyacrylate, solvents, pure zinc dust and pigments of aluminium. Free of CHC and CFC.

This product data sheet has been created according to the most current standard of technology. We do however not guarantee for correctness and completeness. No liability for damages due to improper application. update July 2015

HWR CHEMIE GmbH®, Moosfeldstraße 7, D-82275 Emmering

Telefon 08141 / 51 03 0 ▪ Fax 08141 / 51 03 50 ▪ E-Mail: info@hwr-chemie.de ▪ www.hwr-chemie.de