



## OIL-SAFE G 3

All-purpose absorber

Diatomaceous earth

Item no. 6500

**OIL-SAFE G3** is a safe absorption agent

- for binding of liquid chemicals, oils and other liquids,
- certificated according to guideline BMU dated from 23.04.1998,
- suitable for traffic areas.

**OIL-SAFE G3** is used as a binding agent

- in workshops and industry,
- in petrol stations and car wash facilities,
- wherever oil and liquids can leak.



### Instructions for use:

Spread the absorbing agent on spilled liquids, oils etc., wait for a few minutes, physically remove it and sweep the floor afterwards.

1 kg OIL-SAFE G3 absorbs approx. 1 litre of liquid.

### Advice:

Keep OIL-SAFE G3 dry.

### Characterisation:

#### Appearance:

Ginger coloured granulate material.

#### Grain size distribution:

98.3% between 0.5 – 4 mm; 1.4% between 0.125 – 0.5 mm; 0.3% less than 0.125 mm.

#### Packaging:

Bag (20 kg, equals 41 litres), pallet (36 bags).

#### Certificates of quality:

“Hygiene Institute of the Ruhr Basin”, Gelsenkirchen: attested as harmless from an occupational medicine perspective and in respect of the environment.

“Institute for Materials Testing, North Rhine-Westphalia”, Dortmund: extensive examinations confirm the outstanding properties for binding oils, solvents and other liquids.

This product data sheet has been created according to the most current standard of technology. We do however not guarantee for correctness and completeness. No liability for damages due to improper application. update Oct. 2021

**HWR CHEMIE GmbH®**, Moosfeldstraße 7, D-82275 Emmering

Telefon 08141 / 51 03 0 • Fax 08141 / 51 03 50 • E-Mail: [info@hwr-chemie.de](mailto:info@hwr-chemie.de) • [www.hwr-chemie.de](http://www.hwr-chemie.de)