

MONIL®-STV

Waster Based Stone Protection

Item no. 4705



MONIL®-STV

- is the ideal protection for mineral surfaces after deep-cleaning with item no. 4700 MONIL®-STR
- protects patios, stairs, paving, tomb stones, walls and roofs
- prevents the penetration of water into stone surfaces and frost damage

MONIL®-STV

- is free of hazardous solvents and fluorine compounds
- reduces re-soiling and makes future cleaning easier
- is also suitable for other porous or absorbent surfaces such as wood









Fields of application and recommended dilution:

undiluted

Apply **MONIL®-STV** undiluted using a low-pressure pumping equipment or a brush. All surfaces must be cleaned to remove all traces of dirt before applying MONIL®-STV. Allow surface to dry for at least 24 hours. The process should be repeated for highly stressed surfaces. 1 liter is sufficient for approx. 20 to 40 m², depending on the absorbency of the substrate.

The sealing lasts for several months, depending on the exposure. Use only neutral cleaners (e.g. ALL-CLEAN, item no. 2540) for regular cleaning in order to avoid damage to the sealing.

Deep clean surface before re-applying MONIL®-STV.

A darkening effect of the treated surface might occur after the application.

Chemical Characterization:

Appearance:

Milky liquid with mild odor.

Ingredients:

Mixture of synthetic oils, emulsifiers and preservatives in water.

Free of fluorine compounds, CHC and other solvents.

pH value:

