



OIL-SAFE G 3

Oil and chemical binding agent


Item no. 6500

OIL-SAFE G 3

- is a neutral and safe absorption agent
- easily binds oils, fats, solvents, chemicals, acids and lyes
- does not produce dust, is non-flammable and has a high absorption capacity

OIL-SAFE G 3

- is used as a binding agent in industry, crafts and engineering
- is used by fire brigades in accidents with spilled oil
- is certificated according to guideline BMU from 23.04.1998



Areas of application and recommended dilution:

Spread the absorbing agent on spilled liquids, oils etc., wait for a few minutes, physically remove it and sweep the floor afterwards.

1 kg OIL-SAFE G3 absorbs approx. 1 litre of liquid.

Chemical characterisation:

Appearance:

Light brown granulate.

Grain size distribution:

98.3% between 0.5 - 4 mm; 1.4% between 0.125 - 0.5 mm; 0.3% less than 0.125 mm (virtually dust-free).

Certificates of quality:

Hygienic Institute of Gelsenkirchen: Occupational health and environmental clearance certificates. MPA-NRW (Materialprüfungsamt Nordrhein-Westfalen), Dortmund: Extensive examinations confirm the outstanding properties for binding oils, solvents and other liquids.

Packaging:

Bag (20 kg, corresponds to 41 liters), pallet (36 bags).

Advice:

Keep OIL-SAFE G 3 dry.